

### DESCRIPTION

Total Thickness	EN ISO 24346	7.8mm
Thickness of wearlayer	EN ISO 2434	0.7mm + Polyurethane
Weight	EN ISO 23997	12kg/m <sup>2</sup>
Tile Dimensions	EN ISO 24342	457mm x 457mm 497mm x 497mm
Number of tiles & sqm per box	-	5 / 1.04 sqm 5 / 1.23 sqm

### CLASSIFICATION

Norm / Product specification	-	EN ISO 10582
European classification	EN ISO 10874	34-43
Fire Class	EN 13 501-1	Bfl-s1
Static electrical propensity	EN 1815	<2 kV
Slip Resistance	DIN 16165 app. B (DIN 51130)	R10 Class

### PERFORMANCE

Wear resistance	EN 660.2	<2mm <sup>3</sup>
Wear group	NF 189	T Group
Type Binder Content	ISO 10582	I Group
Curling	EN ISO 23999	≤1mm
Dimensional stability (norm)	EN ISO 23999	≤0.15%
Dimensional stability (average measured value)	-	≤0.10%
Residual indentation	EN ISO 24343-1	<0.05
Castor chair test (type W)	ISO 4918	OK
Shore hardness	EN ISO 868	>60 H <sub>D</sub>
Thermal conductivity	EN ISO 10456	0.25 w/(m.K)
Colour fastness	EN ISO 105 - B02	≥6 degree
Surface treatment	-	PUR+
Chemical products resistance	EN ISO 26987	OK

### ENVIRONMENTAL ACCREDITATIONS

TVOC after 28 days	ISO 16000-6	<100 µg/m <sup>3</sup>
Certification	-	Floorscore®
Recycled content		85% Recycled material

### CE MARKING



EN 14041

